

TAGELUS®

FIBERGLASS SAND FILTER

Making a time-proven technology better.

Sand filters have been installed on tens of thousands of pools for decades—a testament to their performance, value and ease of use. But not all sand filters are equal, because not all include design features that continuously flatten and level the sand inside the tank. This is the key to consistent performance and quicker cleaning cycles that keep pump operating costs low. It is also a key advantage when you select a Tagelus filter.





TAGELUS® FIBERGLASS SAND FILTER

Maximum water clarity with minimal attention.

Tagelus filters remove particles large and small...so small that many are undetectable by the human eye, but in quantity make water cloudy. The reason thousands of Tagelus filters have been installed by pool professionals worldwide is their consistency of performance over time. Plus, they go about their work without making work for you.

KEY FEATURES

Six position Hi-Flow™ valve

Provides easy control of all filter functions and has a manual air relief valve and a sight glass to make inspection, maintenance and operation fast, easy and safer.

One-piece tank

One-piece fiberglass-reinforced tank with UV-resistant surface finish for years of service and exceptional strength.

Combination drain

Combination sand and water drain speeds servicing and winterizing.

Efficient flow system design

Flow system design ensures maximum run times between backwashing to save you time and provide years of service with only periodic backwashing to remove trapped debris from the sand.

Special "diffuser"

Creates a uniform sand bed that consistently traps more dirt without impeding the water flow resulting in more effective filtration and longer run times between backwashing.

Threaded internal parts

For fast and easy service.

Model Number	Filter Area Sq. Ft.	Vertical Clearance*	Filter Diameter	Required Sand† (lbs.)	Flow Rate GPM Res.**	Turnover Capacity (Gallons)		
						8 hrs.	10 hrs.	12 hrs.
TA 40D	1.8	47"	19.5"	175	40	19,200	24,000	28,000
TA 50D	2.3	51.5"	21.5"	225	50	24,000	30,000	36,000
TA 60D***	3.1	57"	24.5"	325	60	28,000	36,000	43,200
TA 100D	4.9	65.5"	30.5"	600	100	48,000	60,000	72,000

*Required clearance to remove the valve.

**Maximum flow rate.

***TA 60D available with 1½" or 2" valve.

†Use standard #20 silica sand

Maximum operating pressure is 50 psi



1620 Hawkins Ave | Sanford, NC 27330 | United States | 800.831.7133 | pentair.com

All Pentair trademarks and logos are owned by Pentair plc, or one of its global affiliates. Tagelus® and High Flow™ are trademarks and/or registered trademarks of Pentair Water Pool and Spa, Inc. and/or its affiliated companies in the United States and/or other countries. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice.

Pentair is an equal opportunity employer.

PI-0115/19 ©2019 Pentair Water Pool and Spa, Inc. All rights reserved.

